

MTBF Report

Identification Data

Name of device	SmartFlex RS232 RS485 WIFI
Order codes	SR308103xx
Sort	LTE Industrial Router
Created, date	Roman Peřura, PDE, May 29, 2018
Authorized, date	Jan Otte, DOE, May 29, 2018

Prediction Method

MIL-HDBK-217F-2, parts count

Prediction Data

Temp	25 °C
FR	8684.2 FITS
MTBF	115152 hours, 13.1 years

SF	33 %
MTBF final	345803 hours, 39.5 years

Op. Time T	5 years
Probability R(T)	88 %
R(T) in -25/+55C	68 %

Explanatory Notes

- Temp** – Temperature at reference conditions.
- FR** – Failure rate: It's the rate of product failures expressed as a function of time.
- MTBF** – Mean Time Between Failures is a prediction of a power supply's reliability.
- SF** – Severity factor: Degree of severity in the event of failure.
- MTBF final** – MTBF including Severity factor.
- Op. time T** – Operating time of interest.
- Probability R(T)** – Probability that the product will operate for the Op. time T without a failure.
- R(T) in -25/+55C** – Probability in specified interval.

This document is know-how of the Advantech B+B SmartWorx s.r.o. company. It may not be handed over to third person or abuse without permit.